

INSTANT REMOVER

INSTANT CLEANER FOR FRESH CONCRETE GROUTING PUTTY



- POLISHED PORCELAIN
TILES
- CERAMICS
- GLASS MOSAIC
- QUARRY TILES

WHAT IT'S FOR

- Removes fresh concrete grouting putty, also with additives.
- Ideal for cleaning the backs of large tiles before laying.
- Ideal for cleaning putty application tools after use.

ADVANTAGES

- RAPID DRY TECHNOLOGY: fast-acting, to be used at the same time as laying.
- Does not foam and does not need rinsing.
- Safe for the user and for the environment.
- Does not affect tiles or grout.
- High coverage.
- Does not ruin profiles in aluminium and steel.
- Does not emit toxic fumes.
- For indoor and outdoor use, on walls and floors.

HOW TO USE IT

No dilution required: ready to use.

Application:

Clean after the excess putty has been removed. **Start when the paste becomes thicker and opaque (usually after between 10 to 30 minutes) in accordance with the times given by the manufacturer.**

Spray **INSTANT REMOVER** evenly across the surface. Leave to act for 1-2 minutes **based on the absorbency of the material.**

Use a damp sponge trowel, rinsing frequently to keep the sponge clean.

In the event of stubborn residues, apply again one hour after the putty was applied, following the instructions above. For curing times, refer to the instructions provided by the putty manufacturer.

COVERAGE

indicative of 750ml bottle

Large format tiles	up to 350 linear metres
Mosaic	Up to 15 m ²

The coverage is indicative and refers to a single coat.

CAUTION:

Do not use on polished marble or on any materials that are sensitive to acids. Carry out a preliminary test on a small area of the surface to make sure that the grouting is resistant to the cleaning product. For items in aluminium, follow the instructions. **Avoid the use of abrasive sponges. do not apply excessive pressure when washing as this could damage the grouting.**

Packaging

750ml bottle with spray nozzle in boxes of 12.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.

TEMPERATURES

Storage temperature: from 5° to 30° C.

The product should be applied to materials with temperature between 5° and 30°C.

LABELLING

Signal words:

Hazard indication:



TECHNICAL FEATURES

Appearance: liquid

Colour: transparent

Odour:

Density: 1.011 kg/l

pH: 1.4

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.