

FILA Industria Chimica Spa
Via Garibaldi, 58
35018 San Martino di Lupari
Padova • ITALY

T +39 049 94 67 300
F +39 049 94 60 753
filasolutions.com
info@filasolutions.com

C.F. | P.IVA IT00229240288
Estero M/PD 016 855
Cap. sociale € 500.000,00 i.v.
R.E.A. Padova 45734



FILA DILUTION CONTROL SYSTEM

The degree of dilution required can be obtained by using one of the 15 calibrated metering tips supplied.

PRODUCT	DILUTION RATIO	CALIBRATION NOZZLES
CLEANER PRO	1:30	RED
	1:50	TAN
	1:100	ORANGE
	1:200	AQUA

PRODOTTO/PRODUCT	DILUTION RATIO	CALIBRATION NOZZLES
PS87PRO	1:10	No tips
	1:20	BEIGE
	1:30	RED

The dilution values given in this table are measured at a flow rate of 4 GPM (16 L/min) supply pressure of 40.61 PSI (2.8 bar), with a suction height of 5 feet (1,5 m).

Warning: opening both dosing taps at the same time leads to a slight reduction in the flow rate and results in changes in dilution rate.



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9105079618

